

## **Storage SuperServer ARS-121L-NE316R**

1U NVIDIA Grace CPU Superchip system supporting NVIDIA BlueField®-3 or NVIDIA Connect®X-7



## **Key Applications**

Software-defined Storage, In-Memory Computing, Data Intensive HPC, Private & Hybrid Cloud, NVMe Over Fabrics Solution,

## **Key Features**


- NVIDIA Grace™ CPU Superchip (Dual-Core), 144 ARM v9 cores, TDP 500W;
- Up to 960GB LPDDR onboard memory;
- 2 PCIe 5.0 x16 FHHL slots & 2 AIOM connector (OCP 3.0 SFF Compliant);
- 16 Front Hot-Swap E3.S (7.5mm) NVMe drive bays;
- Reduntant Titanium 1600W Power Supplies;



Form Factor	1U Rackmount
Tomiruecor	Enclosure: 438.4 x 43.6 x 772.15mm (17.2" x 1.7" x 30.4")
	Package: 672 x 224 x 1100mm (26.46" x 8.82" x 43.31")
Processor	Dual processor(s)
	NVIDIA Dual 72-core CPUs on a Grace™ CPU Superchip
System Memory	Slot Count: Onboard Memory
	Max Memory: Up to 960GB ECC LPDDR5X
Drive Bays Configuration	Default: Total 16 bays
	• 16 front hot-swap E3.S 1T NVMe drive bays
	M.2: 2 M.2 PCIe 5.0 x4 NVMe slots (M-key 22110(default))
Expansion Slots	Default
	• 2 PCIe 5.0 x16 (in x16) FHHL slots
	Option A
	• 2 PCIe 5.0 x16 (in x16) AIOM slots (OCP 3.0 compatible)
On-Board Devices	System on Chip
Input / Output	LAN: 1 RJ45 1 GbE Dedicated BMC LAN port
	USB: 1 USB 3.0 Type-A port(Rear)
	Video: 1 mini-DP port
input / Output	USB: 1 USB 3.0 Type-A port(Rear)



(Front View – System) (Rear View – System)







Fans: 8 Removable heavy-duty 4cm Fan(s)
2x 1600W Redundant (1 + 1) Titanium Level (96%) power supplies
BIOS Type: AMI 64MB SPI Flash EEPROM
CPU: Monitors for CPU Cores, Chipset Voltages, Memory
FAN: Fans with tachometer monitoring
Status monitor for speed control
Pulse Width Modulated (PWM) fan connectors
Temperature: Monitoring for CPU and chassis environment
Thermal Control for fan connectors
Weight: Gross Weight: 66.8 lbs (30.3 kg)
Net Weight: 43.6 lbs (19.8 kg)
Available Color: Silver
Operating Temperature: 10°C to 35°C (50°F to 95°F)
Non-operating Temperature: -40°C to 60°C (-40°F to 140°F)
Operating Relative Humidity: 8% to 90% (non-condensing)
Non-operating Relative Humidity: 5% to 95% (non-condensing)
Super G1SMP
CSE-SG101E3-R000NDP